

DATA SHEET



Single Phase Induction Motor - Squirrel Cage

Customer :						
Product line : Pool Spa Pump Single-Phase Start Capacitor		Product code : 10502538				
		Catalog # : PCJ115				
Frame : L56J	Output : 1.5 HP (1.1 kW)	Poles : 2	Frequency : 60 Hz	Rated voltage : 115/230 V		
Rated current : 17.7/8.85 A	L. R. Amperes : 104/52.2 A	LRC : 5.9x(Code K)	No load current : 10.5/5.25 A	Rated speed : 3450 rpm		
Slip : 4.17 %	Rated torque : 2.28 ft.lb	Locked rotor torque : 130 %	Breakdown torque : 210 %	Insulation class : B		
Service factor : 1.10	Moment of inertia (J) : 0.0361 sq.ft.lb	Locked rotor time : 10s (cold) 6s (hot)	Temperature rise : 70 K	Duty cycle : Cont.(S1)		
		Ambient temperature : -20°C to +50°C	Altitude : 1000 m.a.s.l.	Protection degree : IP21		
		Cooling method : IC01 - ODP	Mounting : F-1	Rotation ¹ : CCW		
		Noise level ² : 58.0 dB(A)	Starting method : Direct On Line	Approx. weight ³ : 29.3 lb		
Output	25%	50%	75%	100%		
Efficiency (%)	63.5	64.5	69.0	69.6		
Power Factor	0.35	0.61	0.72	0.79		
Foundation loads						
Max. traction						
Max. compression						
Bearing type :	<u>Drive end</u> 6203 2RS		<u>Non drive end</u> 6203 2RS			
Sealing :	Without Bearing Seal		Without Bearing Seal			
Lubrication interval :	-		-			
Lubricant amount :	-		-			
Lubricant type :	Mobil Polyrex EM					
Notes						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by						
Date	12/10/2023				Page	Revision
					1 / 1	