



Digital pump driver for 2 pumps systems on duty-standby operation at constant outlet pressure.

DPR alt is a compact device for automatic control and protection of 2 electric pumps systems, up to 2,2 kW (3 HP), multi-voltage (110-230 V) and equipped with an innovative outlet pressure reducing/regulating system. These 2 pumps will operate in **duty-standby operation** mode.

Both pumps are managed and protected by the same *DPR* with alternated starting sequence - they never will operate simultaneously. This system guarantees the flow supply in case of failure of one of the electric pumps and also increase their durability.

DPR alt includes all the same features of an standard **DPR**.









REGISTERED DESIGN





Low Voltage Directive 2014/35/EC Electromagnetic Compatibility 2014/30/EC RoHS 2011/65/EC + 2015/863/EC

DPR alt

OPERATING CHARACTERISTICS

- Duty-stanby operation.
- Power relays to manage 2 electric pumps up to 2,2 kW (3 HP).
- Multi-voltage power supply: 110-230 V.
- Manual regulation of the constant outlet pressure with integrated adjusting tool.
- Outlet pressure indicator with pointer.
- Digital adjustment of the start pressure.
- Digital pressure gauge (bar/psi).
- Inner flow sensor.
- Inner current sensor with instantaneous digital reading.
- Functions: **APR** (Anti-blocking periodic routine), **ART** function (Automatic Reset Test), **Anti- looding**, **Stand-by** mode.
- Protection against: dry-run operation, overcurrent, over-pressure, low-pressure, fast-cycling, flooding, rotor locking.
- Control panel includes: 3-digit display, flow indicator, bar/psi indicator, alarm indicator and push-buttons.
- Register of operation data an alarms.
- Reserve against leaks in the installation.
- Inlet and outlet hydraulic threads: G1"