

# DATASHEET

## Engineered Panels



### Main Features

|              |                 |
|--------------|-----------------|
| Series       | : GPH2          |
| Product Code | : GPH2125QC4000 |
| Type         | : Standard      |

### Basic Data

|                           |                                                                                               |
|---------------------------|-----------------------------------------------------------------------------------------------|
| Panel type                | : SOFT-STARTER                                                                                |
| Bypass type               | : None                                                                                        |
| Enclosure type            | : Wall mount                                                                                  |
| Enclosure rating          | : Type 4                                                                                      |
| Thermal Management        | : None                                                                                        |
| General enclosure options | : None                                                                                        |
| Disconnect switch type    | : Circuit Breaker rotary handle disconnect                                                    |
| Horsepower (HP)           | : 125 HP                                                                                      |
| Main voltage              | : 460 V                                                                                       |
| Control Voltage           | : 120 V                                                                                       |
| Frequency                 | : 60 Hz                                                                                       |
| SCCR rating               | : 5 kAIC                                                                                      |
| Control power transformer | : 100 VA - Open                                                                               |
| Reactor/Filter            | : None                                                                                        |
| Communication             | : None                                                                                        |
| Control options           | : Start Pushbutton, Stop Pushbutton, Hand/OFF/Auto Selector Switch, Run Light and Fault Light |

### Dimensions

|                |                       |
|----------------|-----------------------|
| Nominal height | : 1000.0 mm / 39.4 in |
| Nominal width  | : 600.0 mm / 23.6 in  |
| Nominal depth  | : 350.0 mm / 13.8 in  |

### Certifications

|               |          |
|---------------|----------|
| Certification | : UL/cUL |
|---------------|----------|

### Notes

1) Image merely illustrative;