

ENCLOSED STARTER ESWE-B38V24KX-D14

Catalog Number: **ESWE-B38V24KX-D14** | Product: 11136085

OVERVIEW



Product features

| | | | |
|-----------------------------|--------------------|---------------------------|---------------------------|
| Start Type | Direct Three-phase | Rated operational voltage | Ue<=440V |
| Assembly method (start key) | Plastic Crate | Control voltage | 180-208V50HZ/208-240V60HZ |
| Reference | ESWE | Degree of protection | TYPE4X |
| Maximum Power Rating | Not applicable | | |



Representative Image Only

ENCLOSED STARTER ESWE-B38V24KX-D14

OVERVIEWPRODUCT DETAILSDOWNLOAD CENTER

PRODUCT DETAILS

TECHNICAL DATACAD LIBRARY

| | | | |
|---------------------------|-------------------------------|--------------------------------|-----------------|
| Start Type | Direct Three-phase | Rated current (AC-3) | 38A (CWB38) |
| Maximum Power Rating | Not applicable | Overload relay | 25-32 A (MPW40) |
| Rated operational voltage | Ue<=440V | Measuring tool and accessories | Not Applicable |
| Control voltage | 180-208V50HZ/208-240V60HZ | Button type | Unspecified |
| Control devices | H-O-A+On+Off+Mr+Signal Switch | Button color | Not Specified |
| Degree of protection | TYPE4X | Connection Type | Not Applicable |
| Starters Complements | Does Not Contain | | |