

ENCLOSED STARTER PESW-105V47AX-R44

Catalog Number: PESW-105V47AX-R44 | Product: 10687943

OVERVIEW



Representative Image Only



WEG enclosed starters series were designed to meet the requirements and flexibility frequently demanded in industrial applications. Featuring components that meet IEC design standards and UL horsepower ratings, WEG enclosed starters are UL508A approved and cULus certified. This means your panels will fulfill the rigorous requirements of UL508A and will have the quality and performance as for all WEG products.

Product features

Start Type	Direct Single-phase	Maximum Power Rating	Not applicable
Assembly method (start key)	Plastic Crate	Control voltage	400-415V50HZ/480V60HZ
Reference	PESW	Degree of protection	TYPE4X



ENCLOSED STARTER PESW-105V47AX-R44

OVERVIEW PRODUCT DETAILS DOWNLOAD CENTER

PRODUCT DETAILS

TECHNICAL DATA CAD LIBRARY

Start Type	Direct Single-phase	Rated current (AC-3)	105A
Maximum Power Rating	Not applicable	Overload relay	75-97 A (RW117)
Control voltage	400-415V50HZ/480V60HZ	Measuring tool and accessories	Not Applicable
Control devices	A-On-Off Button	Button type	Unspecified
Degree of protection	TYPE4X	Button color	Not Specified
Starters Complements	Does Not Contain	Connection Type	Not Applicable