

ENCLOSED STARTER PESW-50V47AX-R38

Catalog Number: PESW-50V47AX-R38 | Product: 10716226

Replaced by : PESW-B50D39AX-R71 - 14971338

OVERVIEW



Representative Image Only



WEG enclosed starters series were designed to meet the requirements and flexibility frequently demanded in industrial applications. Featuring components that meet IEC design standards and UL horsepower ratings, WEG enclosed starters are UL508A approved and cULus certified. This means your panels will fulfill the rigorous requirements of UL508A and will have the quality and performance as for all WEG products.

Product features

Start Type	Direct Three-phase	Maximum Power Rating	Not applicable
Assembly method (start key)	Plastic Crate	Control voltage	400-415V50HZ/480V60HZ
Reference	PESW	Degree of protection	TYPE4X



ENCLOSED STARTER PESW-50V47AX-R38

OVERVIEWPRODUCT DETAILSDOWNLOAD CENTER

PRODUCT DETAILS

TECHNICAL DATACAD LIBRARY

Start Type	Direct Three-phase	Rated current (AC-3)	50A
Maximum Power Rating	Not applicable	Overload relay	32-50 A (RW67)
Control voltage	400-415V50HZ/480V60HZ	Measuring tool and accessories	Not Applicable
Control devices	A-On-Off Button	Button type	Unspecified
Degree of protection	TYPE4X	Button color	Not Specified
Starters Complements	Does Not Contain	Connection Type	Not Applicable