

# ENCLOSED STARTER PESW-B9V24AX-R61

Catalog Number: PESW-B9V24AX-R61 | Product: 13438765

OVERVIEW



Representative Image Only



WEG enclosed starters series were designed to meet the requirements and flexibility frequently demanded in industrial applications. Featuring components that meet IEC design standards and UL horsepower ratings, WEG enclosed starters are UL508A approved and cULus certified. This means your panels will fulfill the rigorous requirements of UL508A and will have the quality and performance as for all WEG products.

### Product features

|                             |                    |                           |                           |
|-----------------------------|--------------------|---------------------------|---------------------------|
| Start Type                  | Direct Three-phase | Rated operational voltage | Ue<=600V                  |
| Assembly method (start key) | Plastic Crate      | Control voltage           | 180-208V50HZ/208-240V60HZ |
| Reference                   | PESW               | Degree of protection      | TYPE4X                    |
| Maximum Power Rating        | Not applicable     |                           |                           |



## ENCLOSED STARTER PESW-B9V24AX-R61

OVERVIEWPRODUCT DETAILSDOWNLOAD CENTER

### PRODUCT DETAILS

TECHNICAL DATACAD LIBRARY

|                           |                           |                                |                |
|---------------------------|---------------------------|--------------------------------|----------------|
| Start Type                | Direct Three-phase        | Rated current (AC-3)           | 9A (CWB9)      |
| Maximum Power Rating      | Not applicable            | Overload relay                 | 4-6.3 A (RW27) |
| Rated operational voltage | Ue<=600V                  | Measuring tool and accessories | Not Applicable |
| Control voltage           | 180-208V50HZ/208-240V60HZ | Button type                    | Unspecified    |
| Control devices           | A-On-Off Button           | Button color                   | Not Specified  |
| Degree of protection      | TYPE4X                    | Connection Type                | Not Applicable |
| Starters Complements      | Does Not Contain          |                                |                |