

ENCLOSED STARTER PESWS-65V24AX-RM38

Catalog Number: PESWS-65V24AX-RM38 | Product: 10075656

Replaced by : PESWS-B50V24AX-RM71 - 14970652

OVERVIEW



Representative Image Only



WEG enclosed starters series were designed to meet the requirements and flexibility frequently demanded in industrial applications. Featuring components that meet IEC design standards and UL horsepower ratings, WEG enclosed starters are UL508A approved and cULus certified. This means your panels will fulfill the rigorous requirements of UL508A and will have the quality and performance as for all WEG products.

Product features

Start Type	Direct Single-phase	Rated operational voltage	Ue<=600V
Assembly method (start key)	Plastic Crate	Control voltage	180-208V50HZ/208-240V60HZ
Reference	PESWS	Degree of protection	TYPE4X



ENCLOSED STARTER PESWS-65V24AX-RM38

OVERVIEW PRODUCT DETAILS DOWNLOAD CENTER

PRODUCT DETAILS

TECHNICAL DATA CAD LIBRARY

Start Type	Direct Single-phase	Starters Complements	Does Not Contain
Rated operational voltage	Ue<=600V	Rated current (AC-3)	65A
Control voltage	180-208V50HZ/208-240V60HZ	Overload relay	32-50 A (RW67)
Control devices	A-On-Off Button	Measuring tool and accessories	Not Applicable
Degree of protection	TYPE4X	Connection Type	Not Applicable