

ENCLOSED STARTER PESWS-B9V24AX-RM63

Catalog Number: PESWS-B9V24AX-RM63 | Product: 14888602

OVERVIEW



Representative Image Only



WEG enclosed starters series were designed to meet the requirements and flexibility frequently demanded in industrial applications. Featuring components that meet IEC design standards and UL horsepower ratings, WEG enclosed starters are UL508A approved and cULus certified. This means your panels will fulfill the rigorous requirements of UL508A and will have the quality and performance as for all WEG products.

Product features

Start Type	Direct Single-phase	Rated operational voltage	Ue<=600V
Assembly method (start key)	Plastic Crate	Control voltage	180-208V50HZ/208-240V60HZ
Reference	PESWS	Degree of protection	TYPE4X
Maximum Power Rating	Not applicable		



ENCLOSED STARTER PESWS-B9V24AX-RM63

OVERVIEW PRODUCT DETAILS DOWNLOAD CENTER

PRODUCT DETAILS

TECHNICAL DATA CAD LIBRARY

Start Type	Direct Single-phase	Rated current (AC-3)	9A (CWB9)
Maximum Power Rating	Not applicable	Overload relay	7-10 A (RW27)
Rated operational voltage	Ue<=600V	Measuring tool and accessories	Not Applicable
Control voltage	180-208V50HZ/208-240V60HZ	Button type	Unspecified
Control devices	A-On-Off Button	Button color	Not Specified
Degree of protection	TYPE4X	Connection Type	Not Applicable
Starters Complements	Does Not Contain		